



PRODUCT FEATURES:

- 6mm surface mounted float glass
- Highly reflective and durable
- Surface Mounted
- Ground and polished edges
- Mirror glass conforms to AS 1228/2006
A Grade Safety glass standards when installed correctly
- Manufactured within the standards
to AS/NZ 2208-1996
- Custom sizing available

Overall Dimensions:

Specify "W" width and "H" height. I

- AS 1428.1 compliant sizes below:

450mm x 1000mm

500mm x 1000mm

600mm x 1000mm

OTHER OPTIONS AVAILABLE: (please specify when ordering)

- 1.5mm-10mm Bevel Edge
- Partial Vinyl Backing
- Clip fasteners
- Screw holes - Model is 747I
- 4mm thickness

CONSTRUCTION:

MIRROR: Fabricated of first quality 6mm float glass. Layers of the mirror are Float Glass, Sensitizer, Supersensitizer, Silver Layer, Chemical Protection Coat, Paint Base Coat, Paint Top Coat. Edges ground and polished smooth.

Can be used in environments up to 60 degrees celsius.

INSTALLATION:

MODEL 747: Silicone to wall via a full coverage of recommended silicone.

We recommend using a 'non-acidic' or 'neutral cure' silicone similar to Bostic V60.

Please note: spot fixing will not achieve an A Grade Glass

GUIDE SPECIFICATION:

Frameless mirror shall be of first quality 6mm float glass.

Full coverage of Silicone is to be applied to the full back of the mirror, it will then be classed as an A Grade Safety Glass. Mirror must be adhered to a solid surface with recommended silicone.

