

Bradley

MODEL 832-039-3636

SHOWER CORNER GRAB RAIL LEFT HAND

Options:

832-038-3636

-2 Peened (Safety Grip)

-6 Powdercoat

PRODUCT FEATURES:

- Surface mounted
- 32mm diameter with concealed fixing
- Standard -900MM + 900MM W
- Complies with AS1428.1

For special sizes of all grab bar rails nominate:

(all dimensions centre to centre)

Horizontal (A) =

Horizontal (B) =

Vertical (C) =



PRODUCT DATA:

CONSTRUCTION:

FLANGES: Fabricated of type 304 (18-8), 80mm dia. 13 gauge stainless steel.

ESCUTCHEONS: Fabricated of type 304 (18-8), 22 gauge stainless steel. One-piece drawn construction with exposed surfaces in architectural satin finish. Snap over flanges to conceal mounting screws.

TUBING: Fabricated of type 304 (18-8), 32mm (1-1/4") O.D. 18 gauge stainless steel, seamless construction with exposed surfaces in architectural satin finish. Bent ends of tubing pass through the flanges and are heliarc welded into a single structural unit for maximum strength. Intermediate supports are contour cut and joined by heliarc welding to form an integral part of the grab bar. All welds ground and polished to blend. Mandrel bending process maintains uniform bar diameter.

STRENGTH:


When properly mounted, all Bradley heavy duty grab bar systems meet or exceed the requirements of Australian Standard AS1428.1(2,3), of ANSI Standard A117.1, the ADA and ABA Accessibility Guidelines for Buildings and Facilities (ADAAG) and the Uniform Federal Accessibility Standard (UFAS).

INSTALLATION:

Secure to wall where adequate in-wall backing exists. Use bar as template to locate mounting holes. Drill holes and set anchors as appropriate. Mount grab rail and secure mounting screws. Snap escutcheons into place.

GUIDE SPECIFICATION:

Grab bar shall be fabricated of type 304 satin finish stainless steel with concealed mounting flanges in sizes and configurations as indicated.



Polished (No. 4) satin finish
will not scratch hands
or catch dirt

Mandrel bending
process maintains
uniform
bar diameter

Bar heliarc welded
to flange to form
a single structural
unit for maximum
strength


Mounting holes

18 gauge type 304
stainless steel

Flange escutcheon

Escutcheon snaps over flange
to conceal mounting screws

Flange of 13 gauge type 304
stainless steel



CONCEALED

*50-60mm wall clearance required
under most building design codes