

Bradley

AUSTRALIA

customised excellence

www.bradleyaustralia.com

MODEL 832-101-NC

DROP DOWN GRAB BAR RAIL WITH NURSE CALL PLATE AND LOCKING PIN

Options:

832-101-51-NC with Toilet Roll Holder

-2 Peened (Safety Grip)

-6 White Powdercoat Finish


PRODUCT FEATURES:

- Surface mounted
- Satin finish stainless steel
- Locks in the 'up' position

Back Plate Dimensions

100mm W x 300mm H - Unit Projects 810mm

Details of Locking Mechanism



PRODUCT DATA:

CONSTRUCTION:

TUBING: Fabricated of type 304 (18-8), 32mm (1-1/4") O.D. 18 gauge stainless steel, seamless construction with exposed surfaces in architectural satin finish. Bent ends of tubing pass through the flanges and are heliarc welded into a single structural unit for maximum strength. Intermediate supports are contour cut and joined by heliarc welding to form an integral part of the grab bar. All welds ground and polished to blend. Mandrel bending process maintains uniform bar diameter.

STRENGTH:

When properly mounted, all Bradley heavy duty grab bar systems meet or exceed the requirements of Australian Standard AS1428.1 (2,3), of ANSI Standard A117.1, the ADA and ABA Accessibility Guidelines for Buildings and Facilities (ADAAG) and the Uniform Federal Accessibility Standard (UFAS).

INSTALLATION:

Secure to wall where adequate in-wall backing exists. Use bar as template to locate mounting holes. Drill holes and set anchors as appropriate. Mount grab rail and secure mounting screws.

GUIDE SPECIFICATION:

Grab bar shall be fabricated of type 304 satin finish stainless steel with concealed mounting flanges in sizes and configurations as indicated.

